



19" LED Industrial Monitor with full dimming function, sunlight readable

The Nirolo 19" has a variety of input options suitable for a wide range of applications. Standard with full dimming function from 0 to 100% suitable for marine, offshore, industrial and control room installations. With VGA DVI, BNC, HDMI designed for CCTV. The monitor has a sturdy metal housing, shock and vibration resistant. The modular design ensures this model is available in many variations: rear mount, openframe, panel mount, rack mount, flush mount, glass mount, glass mount with PCAP touch and desktop model. Optional available with SAW Touch, resistive touch, infra red (IR Touch), PCAP Projected Capacitive touch and anti reflection protection glass.

Specifications

Monitor size	19" LED, 5:4, active area 376,3 x 301,1 mm
Brightness, candela/m2	1000
Contrast	800:1
Resolution	1280 x 1024
Response time (ms)	5 ms
Viewing angle	178/178 extra wide viewing angle
Colours	16,7M
Input sources	DVI, VGA, HDMI, BNC
Power	Internal power supply, universal auto sensing AC90 to 260V, 50/60 Hz
Power consumption	32,5 W (stand-by 2W)
Auto setup	Yes
Speakers	Optional
Protection glass	Optional, standard (Glare) and anti-reflection glass
Touch panel	SAW, resistive, infra red and PCAP Projected Capacitive touch
Dimming	Standard 0 to 100% full dimming function
Sunlight readable	Yes
Net weight	6 kg
Dimension without base	425 x 352 x 61 mm
Colour of housing	Black
VESA mount	100 mm
Certification	FCC, CE
Warranty	Two years

Nirolo Professional Displays B.V.

Biesboschhaven Noord 1 b
4251 NL Werkendam
Tel: +31 (0) 183 505064

www.nirolo.nl

Specification subject to change without prior notice

Included Cables:
Power cable, VGA, DVI and HDMI.