



VL12789 (full dimming monitor)

12,1" TFT (touch) modular design

The versatile 12,1" LED monitor VL127D has a modular design, which enables Nirolo to deliver a wide range of products: desktop model, metal housing, rear mount, panel mount, flush mount, glass mount and rack mount model. Fully dimmable from 0 tot 100%). Also in IP65 front or even in full IP68 housing, also seawater corrosion proof. Optional sunlight readable through optical bonding. All touch types are avialable for this monitor such as PCAP, SAW, IR and resistive touch.

Size	12,1" LED backlight
Brightness, candela/m2	500
Contrast	700:1
Resolution	1024*768
Response time (ms)	12
Viewing angle, H/V	160
Colours	262K / 16,2M
Input	DVI.I, s-video, BNC
Power	External 12VDC power supply
Power usage	25 W (2,5 W)
Auto setup / autyoo detect	Yes
Speakers	Yes
Luminance stabilization	Optional
Protection glass	Optional
Touch panel	Optional
Dimming	Yes full dimming
Sunlight readable	Optional
Anti shock	Yes
Nett weight	1,6 kg
Measurements / screen size viewable	245 x 184
Back light hours	50.000
Temperature range	- 30 tot + 70
VESA mount	75 mm
Warranty	2 yersars carry in



Specifications are subject to change without any further notice.

Nirolo Professional Displays B.V.

Biesboschhaven Noord 1 b
4251 NL Werkendam
The Netherlands
Tel: +31 (0) 183 505064

www.nirolo.nl