



## Versatile 17" LED Industrial monitor with full dimming

The Nirolo 17" monitor comes with many inputs: VGA, DVI, HDMI and BNC. Full dimming. Sturdy rugged metal housing. Due to its modular design, it is available in many different versions such as open frame, rear mount, panelmount, rackmount, flushmount, glassmount, glassmount with PCAP touch, chassis, chassis mount and desktop monitor. A wide choice in touchscreens such as SAW Touch, resistive touch, infra red (IR Touch) and PCAP Projected Capacitive touch. Protection glass and or sunlight readable optional.

### Specifications

Size	17" LED, 4:3, effective area 337,92 x 270,34 mm
Brightness, candela/m2	250
Contrast	800:1
Resolution	1280 x 1024
Response time (ms)	5 ms
Viewing angle	170/160
Colours	16,7M
Input	DVI, VGA, HDMI, BNC
Power	Internal, universal auto sensing AC90 tot 260V, 50/60 Hz
Power consumption	32,5 W (stand-by 2W)
Auto setup	Yes
Speakers	Optional
Protection glass	Optional
Touch panel	SAW, resistive, infra red and PCAP Projected Capacitive touch
Dimming	Standard 0 to 100% full dimming functie
Sunlight readable	Optional
Nett weight	5 kg
Size chassis	380,2 x 318,9 x 59,8 mm
Colour housing	Black
VESA mount	75 mm
IT certificates	FCC, CE
Warranty	2 years

### Nirolo Professional Displays B.V.

Biesboschhaven Noord 1 b  
4251 NL Werkendam  
Tel: +31 (0) 183 505064

Specifications subject to change without prior notice