



Olorin VistaLine 17" Monitor

Olorin VLD178 is a highly flexible monitor built from the ground up to meet requirements for a variety input signals, mounting capabilities and access to different options. It is easily customizable to meet each individual application.

With options such as dimming and flush mounting frames, the monitor is suited for different types of marine applications. VLD178 supports both S-video and CVBS for CCTV and is available with a PCAP multi touch panel.

Specification

Display	Screen size, Format	17" (338 x 270 mm), 5:4
	Brightness, candela/m ²	350 cd/m ²
	Contrast	1000:1
	Resolution, Megapixel	1280x1024 1,3 Mpix
	Response time	5 ms
	Viewing angles, H/V	170 / 160
	Color depth	16,7M
	Backlight type	LED
Input signal	Connections	DVI-I, S-video, BNC (CVBS), 3.5mm Audio, RJ45, VGA adapter cable
Power	Power supply	12Vdc, 3,7A
	Power consumption	Approx. 25W Max. / < 2W in stand-by
Functionality	Automatic adjustment	Yes, via OSD.
	OSD for settings	Yes
	Speakers	Yes
	Luminance compensation	ALC
	Pivot	Yes, graphics card dependent.
	Protective glass	Optional, true flat.
	Touch panel	N/A
	Dimming	Optional
	Sunlight Readable	N/A
	DICOM pt. 14 preset	Yes
Standards	IT certificates	CE(EN 60950-1)
Warranty	Replacement warranty	Two (2) years

Appearance

Appearance	Net. weight	Approx. 3.2 kg
	Measurements (WxHxD)	385 x 317 x 62,8 mm
	Product color	Graphite grey
Mounting	Open frame	Optional
	Kensington lock	Yes
	VESA standard	100 mm

Order no. Monitor & Base unit


Item	Order no. Standard
Standard	VLD17806
w/ True flat glass	VLD17806GTF

Order no. Options

Order no.	Item
XAVL17773	Dimming

Order no. Accessories

Order no.	Item
XAVL17012	Base unit, standard desktop
XAVL98200	Multi attachment Slim
XAVL98201	Multi attachment
XAVL98501	External OSD (1 port)
XAVL98502	External OSD (2 ports)
XAVL98504	External OSD (4 ports)
XAVL99035	DVI to VGA & DVI splitter cable
MSLA623B	Table mount arm



Measurements Chassis version

