



Olorin VistaLine 19" Monitor

Olorin VLD198 is a highly flexible monitor built from the ground up to meet requirements for a variety of input signals, mounting capabilities and access to different options. It is easily customizable to meet each individual application.

With options such as dimming, sunlight readable and flush mounting frames, the monitor is suited for different types of marine applications. VLD198 supports both S-video and CVBS for CCTV and is available with a PCAP multi touch panel.

Specification

Display	Screen size, Format	19" 5:4
	Brightness, candela/m2	300 cd/m2
	Contrast	1000:1
	Resolution, Megapixel	1280x1024 1,3 Mpix
	Response time	25 ms
	Viewing angles, H/V	178 / 178
	Color depth	16,7M
	Backlight type	LED
Input signal	Connections	DVI-I, S-video, BNC (CVBS), 3.5mm Audio, RJ45, VGA adapter cable
Power	Power supply	12V External power supply
	Power consumption	30W (2,5W in stand-by)
Functionality	Automatic adjustment	Yes, via OSD.
	OSD for settings	Yes
	Speakers	Yes
	Luminance compensation	ALC
	Pivot	Yes, graphics card dependent.
	Protective glass	Optional, true flat. IP65
	Touch panel	Optional, PCAP Touch panel IP65 USB & RS232
	Dimming	Optional
Standards	IT certificates	CE(EN 60950-1)
	Warranty	Replacement warranty Two (2) years

Appearance

Appearance	Net. weight	4,5 Kgs
	Measurements (WxHxD)	429,2 x 354,21 x 65 mm
	Product color	Graphite grey
Mounting	Open frame	Optional
	Kensington lock	Yes
	VESA standard	100 x 100 mm

Marine Dimming *

Dimming is enabled on this version of the monitor, it is also bundled with extra cables: XAVL99035 and XAVL99041.

